



超级电容产品规格 Super Capacitor Datasheet

叠片型超级电容 (Convolute coin type super capacitor, DJ series)





产品简介(Products introduction)

最大工作电压 Maximum Operating Voltage	容量 Capatance(F)	容量范围 capacitance range	在1kHZ下内阻 Internal resistance at 1kHZ	型号 Part number
5.5V	0.33F	0.264 ~ 0.594F	75	SCDK5R5334

产品参数 (Specifications)

温度范围 Cate	温度范围 Category temp.range		-25 ~+70		
低温特性 Characteristic	容量变化 Capacitance change	初始测定值(+20)的±30%(-25 ~+70) ±30%of initial measured value at 20 (- 25 ~+70)			
s at low temperature	内阻 Internal resisitance	小于初始测定值(+20)的5倍(-25) <5 times of initial measured value at +20 (at -25)			
寿命 endurance	在70 、5.0V.DC加载条件下,1000小时过后, 电容器参数变化 After 1000 hrs application of 5.0V.DC at 70 ,the capacitor shall meet the following limits	容量变化 Capacitanc e change	初始测定值的±30% ±30%of initial measured value at		
		内阻 Internal resisitance	小于初始测定值的4倍 <4 times of initial measured value at +20		
储存寿命 Shelf life	1000小时,电容器参数变化同寿 loa		er 1000hrs storage at +70 ,without d,.,the capacitor shall meet the ecified limits for "endurance".		
耐湿性 Moisture resistance	在70 、相对湿度90%到95%、 无加载的条件下同,储存500小 时,电容器参数变化同寿命栏参数		After 500hrs storage at +55 ,90%to95% R.H.,the capacitor shall meet the specified limits for "endurance".		

电话:+86-755-26742182 传真:+86-755-26741683 中国·深圳市高新技术产业园中区东部大冲阮屋村37栋

邮编:518057

Tel: +86-755-26742182 Fax: +86-755-26741683 Building37,Ruanwu Village,Dachong,high-Tech Industrial Middle-East Park,Shenzhen,China Z ip Code:518057